



PRODUCT DATA SHEET | BRAKE FLUIDS  
**BRAKE FLUID DOT4**

**FIRST FILL BRAKE FLUID DOT 4** is a high quality glycol ether based hydraulic brake fluid. The material composition and performance will ensure the safe and reliable operation of vehicle braking systems, the key points being are a high boiling point exceeds the minimum ERBP and WERBP requirements, therefore minimizing the risk of vapor lock under extreme conditions; optimal viscosity the product ensure that the system remains responsive in very cold conditions whilst preventing leakage and maintaining good lubricity at high operating temperatures.

Fully protects the complete range of metallic components within the braking system against corrosion damage and potential system failure; Promotes the correct rubber swell/hardness of all rubber components to maximize the working life of system seals, ensuring a safe system operation.

Brake Fluid Dot 4 is specifically formulated to exceed the requirements of the internationally recognized hydraulic brake fluid standards. The color of this product is clear and bright without impurities and a high boiling point.

**PROPERTIES**

- FMVSS 116 DOT 4
- SAE J1703
- SAE J1704
- ISO 4925 Class 3&4
- JIS K2233

**PHYSICAL PROPERTIES**

Density at 20°C, kg/l	:	1,040
Viscosity -40°C, mm2/s	:	1400
Viscosity 100°C, mm2/s	:	2,10
Colour	:	Yellow
Boiling point (reflux), °C	:	263
Wet Boiling point, °C	:	165
pH - 50% in ethanol solution	:	8,5



**PACKAGING OPTIONS**

- 20 LTR
- 60 LTR
- 210 LTR
- 1000 LTR

SCAN QR-CODE  
FOR MORE INFORMATION



By product choice always follow the requirements and instructions of the manufacturer.