

**FIRST FILL CERAMIC ADDITIVE** is a (motor) oil additive based on a high-quality, very pure mineral oil. This guarantees good miscibility and compatibility with all common oils, with the exception of rapeseed oils. The added ceramic particles ensure very low friction and do not react with other substances.

Ceramic Additive reduces damage caused by direct metal-to-metal contact, minimizing wear, pitting and stick-slip, among other things.

#### PROPERTIES

- Reduces friction and wear
- Reduces gas- and oil consumption
- Reduces CO<sub>2</sub>-emissions
- Extends engine life
- Increases engine performance
- Improvement of engine elasticity
- Improvement of cold start
- Protects against a low oil level
- Improvement of cold start

#### APPLICATION

Can be added to all types of lubrication systems, such as gearboxes, differentials, engine lubrication and hydraulic systems.

#### PHYSICAL PROPERTIES

Density at 20°C, kg/l	:	0,97
Colour	:	Yellow
Components	:	Mineral oil Ceramics Additives



#### PACKAGING OPTIONS

- 12 X 250 ML
- 5 / 10 / 25 LTR CANS
- 60 / 200 LTR DRUMS
- 1000 LTR IBC

SCAN QR-CODE  
FOR MORE INFORMATION



By product choice always follow the requirements and instructions of the manufacturer.