



PRODUCT DATA SHEET | TRANSMISSION  
**MINCAT SAE 10**

**FIRST FILL MINCAT SAE 10** has been developed for use in Caterpillar friction devices, like power shift transmissions, clutches and brakes and in other drive train components, such as final drives, bevel gears and differentials. This oil is also suitable as hydraulic oil (CAT HYDO ADVANCED 10) in Caterpillar equipment.

**FEATURES**

- Anti-wear and oxidation stability: super protection
- Cold start: excellent fluidity at low temperature

**PERFORMANCE LEVELS**

- ISO 32
- ALLISON C4
- CATERPILLAR TO-2 / TO-4
- EATON VICKERS I-280-S / M-2950-S
- KOMATSU KES 07.868.1
- ZF TE-ML 03C

**PHYSICAL PROPERTIES**

Density at 15°C, kg/l :	0,835
Viscosity 40°C, mPas :	36,3
Viscosity 100°C, mPas:	6,33
Viscosity Index :	125
Flash Point, °C :	230
Pour Point, °C :	-33
BN, mgKOH/g :	9,4 (HCL04)



**PACKAGING OPTIONS**

- 20 / 60 / 208 LTR
- Other packaging options t.b.d.

SCAN QR-CODE  
FOR MORE INFORMATION



By product choice always follow the requirements and instructions of the manufacturer.



PRODUCED IN THE NETHERLANDS

**FIRST FILL, THE FIRST CHOICE**